



DFIT123-31Z-K-PP

1.000 - 8.000 l/h



Typical applications
Plating and process industry

- Features**
- Environmentally safe in-tank installation
 - Compact filter system
 - Sealless pump, can run dry
 - Self priming

- Options**
- Customised mounting plate
 - Suction extension pipe
 - CPVC/PVDF sockets or Hose connection
 - Bag filters
 - SS filter systems






Filter systems series DF90/DF120 - PP/PVDF





| Qmax l/h | Hmax m | Motor kW | Immersion length (mm) | Mounting plate (mm) | Connection outlet | Pump | Chamber | Medium | Material |
|-------------|-----------|-------------|--------------------------|------------------------|----------------------|------------|---------|--------|----------|
| 1800 | 5 | 0,12 | 270 | 315 x 138 | 3/4" hose | DF(IT)92 | 11Z/12Z | K | PP/PVDF |
| 2500 | 5 | 0,18 | | 475 x 250 | d25/DN20 | DF(IT)93 | 31Z/32Z | K / P | PP |
| 2500 | 6 | 0,18 | 400 | 525 x 250 | d25/DN20 | DF(IT) 123 | 31Z/32Z | K / P | PP |
| 4000 | 7 | 0,25 | | 525 x 250 | | DF(IT) 124 | 31Z/32Z | K / P | PP |
| 7000 | 8 | 0,37 | | 570 x 300 | | DF(IT) 125 | 71Z/72Z | K / P | PP/PVDF |
| 9000 | 9 | 0,55 | | 570 x 300 | | DF(IT) 126 | 71Z/72Z | K / P | PP/PVDF |

 www.hendor.com

K = cartridges

Qty x L
 11Z-K = 1 x 10"
 31Z-K = 3 x 10"
 71Z-K = 7 x 10"

P = discs

Qty OD/ID
 31Z-P = 32 x 136/32
 71Z-P = 32 x 205/32